

DANGER: Contains Aliphatic Mineral Spirits (647-41-85-7), Mineral Oil (8042-47-5), Carbon Dioxide Propellant (124-38-0) and Polytetrafluoroethylene (9002-84-0). Use only in a well ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes and prolonged contact with skin. Do not permit product to contaminate tobacco products. Wash hands before smoking. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. Do not permit product to contaminate tobacco products. Wash hands before smoking.

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. IF SKIN CONTACT: Wash with soap and water. If irritation persists seek medical attention. EXCESSIVE INHALATION: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. IF INGESTED: Do not induce vomiting. Seek medical attention immediately.

HAZARD RATING:

Health, 1;
Flammability, 2;
Reactivity, 1;
Personal Protection, B

For further information consult
Material Safety Data Sheet.

**KEEP OUT OF REACH
OF CHILDREN**

24 HOUR MEDICAL/
TRANSPORTATION
EMERGENCY 1-800-255-3924

One Touch

PENETRATING LUBRICANT

**FORTIFIED
WITH MOLY
& PTFE**

Features a
360° Valve*

Contains
NO Chlorinated Solvents

DANGER: EXTREMELY FLAMMABLE VAPOR NET WT.
HARMFUL, CONTENTS UNDER PRESSURE, SEE 11 oz.
OTHER CAUTIONS ON SIDE PANEL. (311 g)

**CONFORMS TO TESTS SPECIFIED IN
ASTM STP 332**

Contains no silicones or chlorinated solvents which affect plastics, lacquers, insulation and paint. Contains Molybdenum disulfide and polytetrafluoroethylene for added pressure and wear resistance.

Forceful jet-spray aids in rapid penetration through rust and corrosion to free frozen parts. Leaves a long lasting, lubricating film which defends against future corrosion.

Provides effective lubrication over a broad range of temperatures and pressures.

***NOTE:** SPECIAL VALVE ALLOWS CAN TO BE SPRAYED WHILE HELD IN ANY POSITION.

DIRECTIONS:

Saturate part and allow to stand for a few minutes before attempting to break free.

For heavily encrusted parts a wire brush may be needed. Apply a light spray to parts prior to reassembly.



UNITED RESEARCH CORP
PHONE: 800.506.6416

www.unitedresearchcorp.com